



# FLAIL MOWER UNI

In Quality We Trust  
 INO Brežice d.o.o.,  
 Krška vas 34/b, 8262 Krška vas,  
 SLOVENIA, EU  
 www.inobrezice.com, ino@inobrezice.si



For farmers and contractors. Flail mower UNI is purposed for heavy duty work on smaller agriculture and communal areas for cutting grass, crop residues, bushes etc. Its construction is rigid, designed for intensive use, with big hammers, for cutting material till 6 cm, appropriate for mid-size tractors. Double spiral rotor for high quality finish decreases maintenance costs and required power during work.



Patented rotor with double spiral distribution of working blades at an angle of 45°. Such setup allows power savings up to 24%. Rotor operates more quietly with less strain on all parts of flail mower. +



Rear gate



Deflectors for wider spreading of mulch.



Easy replaceable counter blade



Hammers as standard, Y knives as option for lightweight tasks.



Option of wheels instead of rear roller.



Model	UNI 155	UNI 185	UNI 205
<b>Technical data</b>			
Working width [cm]	164	186	208
Width [cm]	184	206	228
Power requirements [kW/HP]	29-38/40-50	34-45/45-60	40-52/55-70
MAX diameter of the branches to be mulched *	6 cm	6 cm	6 cm
P.T.O. min <sup>-1</sup>	540	540	540
Rotor min <sup>-1</sup>	2200+	2200+	2200+
Weight with hammers [kg]	432	464	498
No. of hammers [pcs]	14	16	18
No. of Y knives [pcs]	42	48	54
3- point linkage cat.	I. and II.	I. and II.	I. and II.
Gearbox with free wheel clutch	●	●	●
Hammers	●	●	●
Doublespiral rotor	●	●	●
Mechanical offset	●	●	●
Height adjustable rear roller	●	●	●
Rear gate	●	●	●
Counter blade	●	●	●
Floating	●	●	●
Skids	●	●	●
Metal flaps	●	●	●
<b>Options</b>			
Y knives**	○	○	○
Hydraulic offset	○	○	○
P.T.O. 1000 min <sup>-1</sup>	○	○	○
P.T.O. shaft T60	○	○	○
Deflectors	○	○	○
Height adjustable wheels	○	○	○

\* Depends of the sort and moisture of branches.

● Standard ○ Option

\*\*MAX diameter of the branches to be mulched with Y knives is 3cm

