

Flail mower PROFI P400

Professional multipurpose shredder with double transmission suitable for bigger tractors (from 120 to 130 HP).

This shredder is particularly versatile with a broad range of potential use. It is suitable for shredding sunflower, grass, straw, cotton, stalks of corn, beetroot and potato leaves, sugar cane, etc., wooden shoots (up to diameter 8 cm). It is also suitable for pasture renovation and for upkeep open field cultivation in general. Multipurpose and strong, this machine is ideal for big farms and contractors.

All models are standard equipped with Y knives with ventilation blades, rear wheels to adjust the cutting height and with mechanical lengthwise road transport system in order to transport the shredder into roads.



Three point linkage with quick and simple hitch system



Wheels for transport



Support wheels

Rigid frame

Transmission on both sides

Towing hitch

Rear gate

Skids



Y knives as standard, hammers as option.

Counter of working hours



INO Brežice d.o.o.,
Krška vas 34/b, 8262 Krška vas,
SLOVENIA, EU
www.inobrezice.com, ino@inobrezice.si
In Quality We Trust



PROFI P400

Techical data	
Working width [cm]	400
Overall width [cm]	426
Power requirement [kW/KM]	88-95/120-130
Weight [kg]	2250
3-point linkage cat.	II. and III.
P.T.O. 1000 min ⁻¹	●
Rotor min ⁻¹	1930
MAX diameter of the branches to be mulched with hammers*	8 cm
MAX diameter of the branches to be mulched with Y knives*	5 cm
Diameter of rotor axle [mm]	60
Diameter of rotor shaft [mm]	300
Rotor thickness [mm]	10
Cutting diameter [mm]	740
Transmission belts [pcs]	8
Hammers [pcs]	48
Y-knives [pcs]	96
Ventilation blades number**	96
Casing thickness [mm]	8
Side panel thickness [mm]	12
No. of wheels [pcs]	3
Double skin frame (4 mm)	●
Skids	●
P.T.O. shaft	●
Counter-blade	●
Openable rear door	●
Height adjustable wheels	●
Mechanical lengthwise transport system	●
Counter of working hours	●
Gearbox with free wheel clutch	●
Floating	●
Option	
Rear roller Ø 220 mm	○
Hydraulic cylinder to open rear gate	○
Hammers	○

*Depends on the sort and moisture of branches

**only with Y knives

● standard
○ option

